



SAFETY DATA SHEETS

M-21251/E-1

DATE: 21May2015

SUPPLIER ADDRESS: 1290 COMBERMERE STREET

TROY, MI 48083

EMERGENCY PHONE NUMBER: (248) 589-2950

1. CHEMICAL PRODUCT

PRODUCT NAME: CARBON DIOXIDE IN NITROGEN

SYNONYMS: None

2. COMPOSITION, INFORMATION ON INGREDIENTS

Ingredient Name	Formula	CAS#	Concentration	Exposure Limits (PPM)			
				ACGIH	OSHA	MAC	Other
CARBON DIOXIDE	CO2	124-38-9	1-5000 PPM	TLV 5000	PEL 5000	5000	STEL 30000
NITROGEN	N2	7727-37-9	BALANCE	S/A	S/A	S/A	S/A

Note: S/A = SIMPLE ASPHYXIAN

3. HAZARD IDENTIFICATION

*** EMERGENCY OVERVIEW ***

High pressure gas.

Can cause rapid suffocation.

POTENTIAL HEALTH EFFECTS

ROUTES OF ENTRY: Inhalation

ACUTE EFFECTS: Mixture acts as a simple asphyxiant by displacing air necessary for life. Symptoms include rapid respiration, muscular incoordination, fatigue, dizziness, nausea, vomiting, unconsciousness, and death.

CHRONIC EFFECTS: None known

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE: None known

OTHER EFFECTS OF OVEREXPOSURE: None

CARCINOGENICITY (US Only):

NTP - No

IARC MONOGRAPHS - No

OSHA REGULATED - No

4. FIRST AID MEASURES

INHALATION: Immediately remove victim to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen.

EYE CONTACT: None

SKIN CONTACT: None

INGESTION: None

IN EVENT OF EXPOSURE, CONSULT A PHYSICIAN

NOTE TO PHYSICIAN: None

5. FIRE FIGHTING MEASURES

FLASH POINT: Nonflammable

AUTOIGNITION TEMPERATURE: N/Ap

FLAMMABLE LIMITS: Nonflammable

LOWER:

UPPER:

EXTINGUISHING MEDIA: Use what is

appropriate for surrounding fire.

SPECIAL FIRE FIGHTING INSTRUCTION AND

EQUIPMENT: Wear self-contained breathing

apparatus and full protective clothing.

Keep fire exposed cylinders cool with

water spray. If possible, stop the

product flow.

HAZARDOUS COMBUSTION PRODUCTS: None

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Cylinder rupture may occur under fire

conditions.

6. ACCIDENTAL RELEASE MEASURES

CLEAN UP PROCEDURES: Evacuate and ventilate area. Remove leaking cylinder to exhaust hood or safe outdoor area. Shut off source if possible and remove source of heat.

SPECIALIZED EQUIPMENT: None

7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING: Secure cylinder when using to protect from falling. Use suitable hand truck to move cylinders.

PRECAUTIONS TO BE TAKEN IN STORAGE:

Store in well ventilated areas. Keep

valve protection cap on cylinders when

not in use.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

ENGINEERING CONTROLS: Provide adequate general and local exhaust ventilation to avoid asphyxiation.

PERSONAL PROTECTION

EYE/FACE PROTECTION: Safety glasses

SKIN PROTECTION: None

RESPIRATORY PROTECTION: In case of leakage, use self-contained breathing apparatus.

OTHER PROTECTIVE EQUIPMENT: Safety shoes when handling cylinders.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Colorless

ODOR: Odorless

PHYSICAL STATE: Gas

VAPOR PRESSURE: N/Ap

VAPOR DENSITY (AIR=1): 0.967-0.970

BOILING POINT (C): N/Ap

SOLUBILITY IN WATER: cm³/100cm³ H₂O
1.485

SPECIFIC GRAVITY (H₂O=1): Gas

EVAPORATION RATE: Gas

ODOR THRESHOLD: None

10. STABILITY AND REACTIVITY

STABILITY: Stable under normal storage conditions.

CONDITIONS TO AVOID: Storage in poorly ventilated areas. Storage near a heat source.

MATERIALS TO AVOID: Nitrogen reacts with Li, Nd, and Ti at high temperatures.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION: None

11. TOXICOLOGICAL INFORMATION

LETHAL CONCENTRATION (LC₅₀): None established

LETHAL DOSE 50 (LD₅₀): N/Ap

TERATOGENICITY: N/Ap

REPRODUCTIVE EFFECTS: N/Ap

MUTAGENICITY: N/Ap

12. ECOLOGICAL INFORMATION

No adverse ecological effects are expected.

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of non-refillable cylinders in accordance with federal, state and local regulations. Allow gas to vent slowly to atmosphere in an unconfined area or exhaust hood. If the cylinders are the refillable type, return cylinders to supplier with any valve outlet plugs or caps secured and valve protection caps in place.

14. TRANSPORT INFORMATION

CONCENTRATION: 1-5000 ppm

DOT DESCRIPTION (US ONLY):

PROPER SHIPPING NAME: Compressed gas,
n.o.s.

HAZARD CLASS: 2.2 (nonflammable)

IDENTIFICATION NUMBER: UN1956

REPORTABLE QUANTITIES: None

LABELING: NONFLAMMABLE GAS

ADR/RID (EU Only): Class 2, 1A

SPECIAL PRECAUTIONS: Cylinders should be transported in a secure upright position in a well ventilated truck.

15. REGULATORY INFORMATION

OSHA: Process Safety Management: Minor component is not listed in appendix A of 29 CFR 1910.119 as a highly hazardous chemical.

TSCA: Mixture is not listed in TSCA inventory.

SARA: The threshold planning quantity for this mixture is 10,000 lbs.

EU NUMBER: N/Ap

NUMBER IN ANNEX 1 OF DIR 67/548: Mixture is not listed in annex 1.

EU CLASSIFICATION: N/Av

R: 20

S: 9, 23

16. OTHER INFORMATION

OTHER PRECAUTIONS: Protect containers from physical damage. Do not deface cylinders or labels. Cylinders should be refilled by qualified producers of compressed gas. Shipment of a compressed gas cylinder which has not been filled by the owner or with his written consent is a violation of federal law (49 CFR).

ABBREVIATIONS:

N/Ap - Not Applicable

N/Av - Not Available

SA - Simple Asphyxiant

NE - None Established

DISCLAIMER: Information included in this document is given to the best of our knowledge, however, no warranty is made that the information is accurate or complete. We do not accept any responsibility for damages by the use of the document.