

## Edgertronic High Speed Color Camera SC1

### Rental and Application Notes

- I/Os: 10/100 Ethernet, 2 USB ports, external trigger, multi-camera genlock
- 12 VDC Power, 2.5/5.5mm locking connector 1.5A SC1, 2.5A SC2/SC2+/SC2X
- Type III Hard Anodize Aluminum enclosure
- Trigger button and 4 status LEDs
- Accepts Nikon F-mount lenses (manual and D series)
- Built in fan



	Specifications
<b>Weight</b>	862 gr Excluding Lens
<b>Dimensions</b>	111mm x 108mm x 79mm Excluding Lens
<b>Video memory</b>	8 GB or 16 GB
<b>Exposure</b>	1/10 to 1/250,000 sec
<b>ISO range [1]</b>	Color – 1,600 to 25,600 Mono – 6,400 to 102,400
<b>Supported resolutions</b>	192 x 96 to 1280 x 1024
<b>Maximum Frame Rate @ Minimum Resolution</b>	17,791 fps @ 192 x 96 22,336 fps @ 192 x 96(Overclocked)
<b>Maximum Frame Rate @ Maximum Resolution</b>	494 fps @ 1280 x 1024 621 fps @ 1280 x 1024(Overclocked)
<b>Enhanced dynamic range</b>	5 settings
<b>Subsampling</b>	Yes
<b>Overclock</b>	5 settings 0% to around 40%
<b>CMOS sensor active area</b>	17.92 x 14.34 mm